

PHOENIX Multi Purpose Low Pressure Rubber Hoses - LP Hoses
Construction
Core : Inner tube of rubber

Reinforcement : Single braid of GI / Steel wire

Application : L.P hose has an excellent temperature characteristics both in high and low temperature, Excellent chemical resistance, non contamination properties, low coefficient of friction and resists deterioration. Therefore the hose is used generally in application.

Temperature Range : Continuous: -20°C to +80°C




Ordering Code -
LP - Size - Length
EX - LP-14-300 (for 1/4" BSP Connection with 300mm long hose)
LP

Length	Size					
	1/8" & 1/4"	3/8"	1/2"	3/4"	1"	1-1/4"
mm	bsp	bsp	bsp	bsp	bsp	bsp
300	40.00	60.00	76.00	138.00	210.00	558.00
500	47.00	69.00	87.00	163.00	235.00	600.00
600	49.00	72.00	93.00	186.00	264.00	612.00
750	54.00	79.00	101.00	198.00	300.00	636.00
1000	63.00	91.00	115.00	252.00	312.00	660.00
1250	72.00	107.00	130.00	278.00	336.00	696.00
1500	79.00	114.00	148.00	300.00	384.00	732.00
1750	87.00	126.00	159.00	330.00	432.00	768.00
200	96.00	137.00	173.00	336.00	468.00	800.00
2500	112.00	161.00	202.00	396.00	510.00	900.00
3000	156.00	185.00	231.00	456.00	588.00	960.00
4000	200.00	230.00	288.00	552.00	756.00	1140.00
5000	230.00	275.00	346.00	675.00	948.00	1330.00
W.P	200 psi	200 psi	150 psi	100 psi	100 psi	50 psi