



Features :-

- Exceptional flexibility allows a lower degree of tubing curvature radius.
- Durable, light weight, abrasion resistant, chemical resistant, and cost-effective.
- Ideal for pneumatic connections in low ambient temperature conditions.
- Self-retracting and self-storing coil tube characteristics with excellent memory.

Applications :-

- Robotics
- Air tools
- Pneumatic systems
- Analytical Instrumentation

Applicable Fluid Type	AIR (No other type of gas or liquid) Do not use in water application	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5in Hg	-750mmHg(-750Torr)
Working Temperature Range	32~140°F	0~60°C

Item Code	Tube ID x OD		Std Roll	Blue	Transparent
OD	mm	mm	Length	Per Mtr	Per Mtr
PUCDC23	2	3	200 mtr	77	77
PUCDC254	2.5	4	200 mtr	32	—
PUCDC46	4	6	100 mtr	57	—
PUCDC58	5	8	100 mtr	91	—
PUCDC6510	6.5	10	100 mtr	136	—
PUCDC812	8	12	100 mtr	184	—
PUCDC1014	10	14	50 mtr	360	—
PUCDC1116	11	16	50 mtr	390	—

➔ **HSN 39173990**