

Phoenix Rubber Hose for Air/Pneumatic IS : 446-1987 Type II

construction:

Lining : NR/SBR compound, smooth & seamless.

Re-enforcement: Braided/Spiral piles of synthetic yarn of high tenacity.

Cover: NR/SBR compound . Black in colour, weather and abrasion resistant . Fabric Wrap finish

Properties:

- Seamless
- Uniform Thickness
- Flexible

Temperature Range

Continuous: -20°C to +85°C

Application:

Recommended for use in compressed air in construction, industries, ship yards etc.



Rubber Pneumatic Hose

Item Code	ID	ID	OD	W.P	W.P	B.P	B.P	Std Length	Price
	inch	mm	mm	psi	bar	psi	bar	mtr	Per Mtr
14-PT	1/4"	6.4	12	290	20	900	62	—	95.00
516-PT	5/16"	7.9	14	290	20	900	62	—	120.00
38-PT	3/8"	9.5	18	290	20	900	62	—	125.00
12-PT	1/2"	12.7	22.7	290	20	900	62	—	140.00
58-PT	5/8"	15.9	26	290	20	900	62	—	220.00
34-PT	3/4"	19	30	290	20	900	62	—	230.00
1-PT	1"	25.4	37	290	20	900	62	—	275.00