

**Construction:**

### Features:

- ### Application:

**Pressure:**

- Temperature Range:** +10°C to +60°C



\* Recommended maximum working temperature : 60/70° C



GEMINI Grey - HD PVC Hoses are made by adequate reinforcement secured by proper placement of hard spirals of rigid PVC in soft PVC wall that imparts strength and flexibility.

### Key Features:

- Abrasion resistant
- No kinking, bulging or bursting even in the most rigorous working conditions
- Excellent resistance to high vacuum/pressure and external impact

### Application:

- Heavy Duty Suction and Delivery of abrasive materials in industries like coal & mineral in mines, stone & lime in quarries, shipping, sewerage disposal, aqua culture, paper mills, cement, chemicals, petrochemicals, oil exploration, construction, fire-fighting equipments, etc.

### Pressure at 30°C:

- Working Pressure 2.5kg/cm<sup>2</sup> to 8kg/cm<sup>2</sup>
- Bursting Pressure 10kg/cm<sup>2</sup> to 25 kg/cm<sup>2</sup>


### Colour:

- Grey

### Temperature Range:

- +10°C to +60°C

**Heavy Duty  
(Grey)**



*Gemini*  
**GREY - HD**

## GS

Item Code	ID inch	ID mm	Thickness mm	W.P @ 30°C bar	Std Length mtr	Price Per / mtr
GS-34	3/4"	20	3	8	30	110.00
GS-1	1"	25	3	8	30	135.00
GS-114	1-1/4"	32	3	7	30	175.00
GS-112	1-1/2"	40	4	5.5	30	230.00
GS-2	2"	50	5	4.5	30	355.00
GS-212	2-1/2"	60	5.5	4.5	30	455.00
GS-3	3"	75	5.5	4.5	30	555.00
GS-4	4"	100	6.5	4	30	945.00
GS-5	5"	125	7	3	15	1800.00
GS-6	6"	150	8.5	2.5	15	2150.00
GS-8	8"	200	11	2.5	6	on request
GS-10	10"	250	15	2.5	6	on request
GS-12	12"	300	20	2.5	6	on request

\* Recommended maximum working temperature : 60/70° C