



### **Characteristics:**

Generally good UV and ozone resistance, Very smooth bore, good abrasion resistance, resistant to oil and petrol, non toxic, free of halogen and softeners, resistant to hydrolysis and microbes

Acc. to TRGS 727 and ATEX 2014/34 EU, with earthing at both ends of the spiral for non- flammable dusts and bulks solids in Zone 22. Gases and liquids with low conductivity of electrostatic charges in Zone 2

### **Applications:**

Danger zones, which require electrically conductive hoses, special hose for industrial vacuum cleaners in explosion-protected areas, suction of coarse-grained media with high flow rate, suction & transport hose for abrasive solids, liquids and gases, protective hose against mechanical wear, oil mist extraction/suction.

# Technical Properties

# TYPES Wall Abrasion Resistance (ISO 4649) Thickness Wire

## **Working Temperature**





Item Code	ID	Vacuum	Pressure	Std Length	Price
	mm	bar	bar	mtr	Per Mtr
UVRH-1	25	0.52	1.38	20	975.00
<b>UVRH-114</b>	32	0.52	1.38	20	1200.00
UVRH-112	40	0.43	1.19	20	1500.00
UVRH-2	51	0.33	1.14	20	1900.00
UVRH-55	55	0.29	1.09	20	2050.00
UVRH-212	63	0.29	1.09	20	2700.00
UVRH-3	76	0.22	1.00	20	2900.00
UVRH-4	102	0.22	0.67	15	3850.00