Pulse Valves

Pilot Operated Pulse Valve

Design to redefine dust collector. They are treasured among the clients for its exceptional attributes and durable performance.









Solenoid Valve - Dust Valve - RMF Series



PHOENIX Dust Collector valves have been specially designed for use in dust collector systems. The high-flow fast-opening 2-way valves are used for pulsing large volumes of air into filter bags for particulate removal.

Features

• Specially designed for reverse jet-type dust collector systems

• High flow Cv(s) to 140 for effective bag cleaning

• High cycle life

Fast opening/closing

Pressure Range: 0.5 To 8.5 Bar **Temperature:** Up to 90 C

Media: Air

Operating voltages: AC: 24, 110, 220

DC:12,24



Construction

Body: Aluminium Die Cast

Seal: NBR

Diaphragm: NBR

Ambient Temperature : -18°C to 85°C

Item Code	Thread	Price	
	inch	Per Nos	
RMF-20	3/4"	2105	
RMF-25	1"	2105	
RMF-40	1-1/2"	3650	

* Guaranteed Quality

→ HSN 848120

Item Code	For	Price		
	Model	Per Nos		
RMFDP-20	RMF-20	530		
RMFDP-25	RMF-25	530		
RMFDP-40	RMF-40	1980		
Item Code	Coil	Price		
	Voltage	Per Nos		
RMFCL-220	AC220V	860		
RMFCL-24	DC24V	860		

SPARES FOR - RMF



Auto Drain Valve

PHOENIX Auto Drain Valves are timer based automatic drain valves. Draining of Compressed air equipment such as Air Receivers, Moisture Separators, Filters, etc. is commonly done by low cost, timer - operated Auto Drain Valves. While these are effective in their functioning, they will open at the set time for condensate to be drained out.













CS-720

DIGI CS-720

SSADV15

CS-\$20

TIMER

DIGI TIMER

	510100720	****			2101 11111211
Item Code	Description		W.P	Thread	Price
	→ HSN 848	3120	Kg/cm²	inch	Per Nos
CS-720	Auto Drain Valve with Timer + Stainer + Ball Valve			1/2"	2000
DIGI CS-720	Auto Drain Valve with Digital Timer + Stainer + Ball Valve			1/2"	4080
SSADV15	Stainless Steel (SS304) Auto Drain with Stainer			1/2"	4900
CS-S70	Stainer + Ball Valve				500
TIMER	ER TIMER - Manual Double Setting - ON 5 sec, OFF 0-30 min				
DIGI TIMER	TIMER TIMER - Digital Double Setting - ON 5 sec, OFF 0-30 min				2850
CSCL	Spare Coil 220v AC				725