

PHOENIX PTFE Seal Tape is produced from pure PTFE. Higher the density of PTFE Thread Sealing Tape, more will be the flexibility and improved diffusion seal capability and easier to work with. Polytetrafluoroethylene Thread Seal Tape is used for sealing threaded joints. It is widely used in water plants, cooling and steam system, system of compress air etc.



PHOENIX Thread Seal Tape

Item Code	Size	Length	MOQ	Price
T T	mm	mtr	nos	Per Nos
TT12	12	12 mtr	1000	20.00
TT19	19	12 mtr	1000	30.00
TT25	25	12 mtr	1000	38.00



Made from durable virgin Teflon. It can be wound around threads of any metal, plastic or rubber pipes to provide leak-free joints that will never freeze or harden with age. This tape is suitable for applications under ambient conditions with all common fluids and gases up to 80 bar gauge for pipes. This tape is suitable for applications in range **-20°C to 200°C** for pipe sizes up to 50 mm.



Specication :-IS-14643.1999
High Quality

HEAVY

FEROLITE Thread Seal Tape

Item Code	Size	Length	MOQ	Price
T T	mm	mtr	nos	Per Nos
FTT12	12	12 mtr	400 nos	46.00
FTT19	19	12 mtr	400 nos	55.00
FTT25	25	12 mtr	400 nos	87.00

